

PAT-NO: JP02000059324A

DOCUMENT-IDENTIFIER: JP 2000059324 A

TITLE: BROADCAST TRANSMITTER FOR  
VOICE GUIDANCE BROADCAST  
SYSTEM AND VOICE GUIDANCE  
BROADCAST SYSTEM

PUBN-DATE: February 25, 2000

INVENTOR-INFORMATION:

NAME	COUNTRY
INOUE, HIROYUKI	N/A

ASSIGNEE-INFORMATION:

NAME	COUNTRY
NABCO LTD	N/A

APPL-NO: JP10224409

APPL-DATE: August 7, 1998

INT-CL (IPC): H04H001/00, G08G001/005

## ABSTRACT:

**PROBLEM TO BE SOLVED:** To simply attain voice guidance by installing plural broadcast transmitters at proper positions in a building, broadcasting a signal to the neighborhood of the installed positions in a limited area and allowing an FM radio or the like to receive the broadcast.

**SOLUTION:** The broadcast transmitter 1 for a voice guidance broadcast system is provided with a high frequency transmission circuit B that transmits a carrier radio wave with a specific frequency that is frequency-modulated by a set voice guidance and an attenuator 13 that adjusts an output level of the carrier radio wave emitted by the high frequency transmission circuit B. Thus, the broadcast area can be limited.

**COPYRIGHT:** (C)2000,JPO